

DriveMaster 2010 Enterprise SAS/FC Tech Specs and System Requirements

ULINK Technology, Inc.

ULINK's DriveMaster 2010 Enterprise SAS/FC (DM 2010 Ent SAS/FC) Serial consists of two products:

- DM 2010 Ent SAS/FC Single
- DM 2010 Ent SAS/FC Network, which includes License Server & Client Station

DriveMaster 2010 Enterprise SAS/FC Specs

- Conform to SCSI Primary Command v4
- Conform to SCSI Block Command v3
- Support standard & user defined SCSI commands
- C-like script language
- Microsoft Windows interface

System Requirements

DM 2010 Ent SAS/FC Single & DM 2010 Ent SAS/FC Network Client Station

- Operating System: Windows 7, Windows 7, Windows Vista, Windows XP, Server 2008 or Server 2003
- CPU: Duo Core or above, hyper-threading is recommended
- RAM: minimum 1 GB
- 32 MB or above video card
- System Drive: Minimum 100MB free space

DM 2010 Ent SAS/FC Network License Server

- Operating System: Windows XP and above
- System Drive: Minimum 5MB free space
- A network card

Hardware Platform Supported by DriveMaster 2010 Enterprise SAS/FC

- **SAS HBA**
 - Adaptec SAS 3405
 - ATTO SAS H680
 - LSI SAS 1064, 1064E, 1068, 1068E, 1078, 2008, 2108, 9260
 - Marvell 6320, 6340, 6440, 6445, 6480, 6485, 9480, 9485

- **FC HBA**
 - LSI FC 919X, 929X, 939X, 949X, 949E
 - QLogic FC 2432
 -

Recommendations for DM 2010 Ent SAS/FC Single & DM 2010 Ent SAS/FC Network Client Station

In order to run DriveMaster 2010 Enterprise SAS/FC to its premium, here are some of hardware recommendations:

- CPU: Intel® Core 2 Quad E6600 or above
- HBA: LSI 1064E, or ATTO H680
- RAM: 2 GB DDR2/DDR3 or above
- Video Card: ATI Radeon X300 Series express video card or above
NVIDIA GeForce 7 Series express video card or above

